

SERIE 120.80

HP 30/80 - KW 22/58

10/50 cm- 4/20 in



3p. Cat I-II



1456

Mod.	cm	↔	in	HP min / max	KW min / max	N. 🗑️	kg	Lb
B 904 L	90		35	30/80	22/58	8	530	1169
B 1004 L	100		39	30/80	22/58	8	540	1191
B 1104 L	110		43	30/80	22/58	8	550	1213
B 1306 L	130		51	35/80	26/58	12	670	1477
B 1456 L	145		57	35/80	26/58	12	690	1521
B 1606 L	160		63	38/80	27/58	12	700	1543
B 1808 L	180		71	40/80	29/58	16	820	1808
B 2008 L	200		79	45/80	33/58	16	840	1852



PdF 540= I 145 II 167 III 206 RpM

OPTIONAL

RUOTE CILINDRICHE - Cylindrical wheels - Roues dentées
 cylindriques - Ruedas cilíndricas - Zylinderförmige Räder



x Serie

	cm	∅ x ↔	in
150.75/95 B 120	40x10		16x4
150.75/95 B 120	40x20		16x8
150.150/200 180 B 160	50x15		20x6
150.150/200 180 B 160	50x21		20x8 1/4
150.150/200 180 B 160	50x30		20x12
220	50x15		20x6
220	50x21		20x8 1/4
220	50x30		20x12